

iPro Vision WH-R330 Fixed Network camera

Waterproof outdoor IP camera, Night Vision

The iPro Vision WH-R330 network camera is equipped with infrared sensor for day and night video surveillance solution, applications for outdoor in dark condition. The fixed camera is equipped with a built-in web server enables a real-time monitoring and video recording requirements, and especially well-suited for uses in distributed video surveillance systems applications. In addition, the network camera with intelligent functions includes motion detection, Email alarm and external I/O, combination of innovation and reliability, provide 24/7 all-weather video surveillance solutions.

In the standard of security, the captured image must be vivid and recognized to users. Therefore, the WH-R330 network camera with 530 TV Lines high resolution provides a very detailed video captured images, enables the recognition of the captured objects. Even in the low light condition, 0.5 LUX still produces good image quality and reveals the clearness of the images. The network camera also features smart intelligent functions, include auto backlight, electronic shutter, and white balance enhance camera flexibility and performance.

Enhancement of camera performance

- Green design
- Corrosion proof
- Improved blower
- Long service life LED
- 100% passed durability test
- Innovated and practical design
- Temperature test, voltage protective test



Highlights

- ▶ Night vision function with infrared LEDs
- ▶ Auto Electronic Shutter
- ▶ IP66 standard with waterproof protection
- ▶ Provide clear image and outstanding quality images
- ▶ Sharp 530 TV lines
- ▶ Provide for Indoor and outdoor applications
- ▶ Video stream up to 25~30 fps per second
- ▶ Dual MPEG4 & MJPEG stream compression
- ▶ Ideal for *Day/Night* surveillance application

Reliability Test


- Color Testing
- Vector Testing
- Frequency Testing
- Video Quality Testing



Image System	
Image Sensor	1/3" Color Super HAD CCD
Picture Pixels	NTSC: 410,000. pixels PAL: 470,000. pixels
Video Compression	MJPEG & MPEG-4 ASP hardware compression
Resolution	QCIF(160x112/NTSC ; 176x144/PAL) CIF(352x240/NTSC ; 352x288/PAL) D1(720x480/NTSC ; 720x576/PAL)
Image FPS	30fps at full D1 resolution(NTSC) 25fps at full D1 resolution(PAL)
Video	
Sync-sync	External
Lens	Standard 8mm Lens
Iris control	No
H-Resolution	530 TV lines
Min illumination	0.2 Lux/ F1.2
S/N ratio	More than 48 dB
Electronic Shutter	NTSC: 1/60 ~ 1/100,000 PAL: 1/50 ~ 1/110,000
Back light Comp.	Auto
White Balance	Auto
Infrared LEDs (Night Vision)	Yes
I/O Interface	
Network	RJ-45 x1
Analog Video Output	BNC connector x 1

Communication	
Ethernet system	10/100base-T x1 for LAN
Protocol supported	TCP/IP , UDP , HTTP , ARP , PPPoE , DDNS , IGMP
QoS	Layer 2,3
Simultaneous Access	10 User
Power	
Power	AC100V ~ AC240V
Operating environment	
Built-in blower	Yes
Outdoor Protected	IP66 Waterproof
Operating Temperature	-25 °C ~ 50 °C
Storage Temperature	-25 °C ~ 50 °C
Humidity	RH 95%
Dimension (Ø x H)	267.5mm x 111mm x115.3mm
EMI	
CE, UL	

Dimensions:



Waterproof Test

Protection Classification IP 66 to DIN EN 60529

- Protection against a wire touching dangerous parts.
- Sealed against dust
- Protection against powerful water jet



World Helmsman Technology Co., Ltd.

3F-5, No. 81, Sec. 1, Hsin Tai Wu Rd., Hsichih, Taipei Hsien 22101, Taiwan

Tel: +886-2-2906-0816 Fax: +886-2-2904-1360

www.wh-tech.com / Email: sales@wh-tech.com

■ DISTRIBUTED BY **CE FC**

