

iPro Astro WH-S330-O PTZ Network camera

Low light conditions, 26x Optical zoom, Day/night surveillance

The iPro Astro WH-S330-O PTZ network camera equipped high sensitivity Ex-View CCD sensor, combine superb 26x optical zoom, designed for wide range and outdoor environment surveillance applications, such as parking lot, harbor, public area, and government.

The WH-S330-O PTZ camera use IR filter technology, support day and night surveillance, even in low light conditions. With built-in web server base on IP standard, support both analog and IP network, increase flexibility and easy to manage with the existing traditional CCTV system and remote monitoring over IP network, for use with distributed video surveillance system applications.

The WH-S330-O PTZ camera use both MPEG4 and M-JPEG compression, for optimized image quality and minimized bandwidth. The PTZ camera is easily installed combine performance and reliability for harsh condition application, to meet you 24/7 security surveillance.



Highlights

- ▶ Clear **480** TV Lines
- ▶ **DSS** (Digital Slow Shutter)
- ▶ **WDR** (Wide Dynamic Range)
- ▶ Built-in **Day& Night** Function
- ▶ Powerful **Pan/Tilt/Zoom** function
- ▶ Vandal-Proof Dome Cove (Max load 380kg)
- ▶ High definition **26x optical zoom**
- ▶ Advanced 1/4" Color **Ex-View** CCD Sensor
- ▶ Dual **MPEG4 & MJPEG** stream compression
- ▶ Protection Classification **IP 66** to DIN EN 60529



Powerful 26x Optical Zoom

- Auto Iris and Auto Focus
- Superb optical design
- High contrast images
- Wider dynamic range

| Image System | |
|-----------------------------|---|
| Image Sensor | 1/4" Ex-View CCD |
| Picture Pixels | NTSC: 410,000. pixels PAL: 470,000. pixels |
| Video Compression | MJPEG & MPEG-4 ASP hardware compression |
| Resolution | QCIF(160x112/NTSC ; 176x144/PAL) CIF(352x240/NTSC ; 352x288/PAL) D1(720x480/NTSC ; 720x576/PAL) |
| Image FPS | 30fps at full D1 resolution(NTSC) 25fps at full D1 resolution(PAL) |
| Video | |
| Sync-sysnc | Internal / External |
| Lens | f=3.5mm to 91.0mm F=1.6 to 3.8 |
| Optical Zoom | 26x Optical Zoom |
| Digital Zoom | 12x (312x Digital Zoom) |
| Focus system | Auto / Manual |
| Iris system | Auto / Manual |
| H-Resolution | 480 Lines at NTSC/ PAL |
| Min illumination | 1.0Lux at F1.6 in Color; 0.01Lux at F1.6 in B/W |
| S/N ratio | More than 50 dB |
| Shutter | Auto , 1/60(50)~1/100,000.sec |
| Wide Dynamic Range | Yes |
| Digital Slow Shutter | Yes |
| Day & Night | Yes |
| I/O Interface | |
| Network | RJ-45 x 2 |
| Analog Video Output | BNC connector x 1 |

| Communication | |
|------------------------------|---|
| Ethernet system | 10/100base-T x2 for LAN/WAN |
| Protocol supported | TCP/IP , UDP , HTTP , ARP , PPPoE , DDNS , IGMP |
| QoS | Layer 2,3 |
| Simultaneous Access | Unlimited(multicast) |
| WAN | WAN for FTTP , Cable modem or xDSL connectivity |
| Pan / Tilt | |
| Pan movement | 0° ~ 360° continuous endless |
| Tilt movement | 0° ~ 90° |
| Pan manual speed | 0.5°/Sec to 80°/Sec vari-speed |
| Tilt manual speed | 0.5°/Sec to 40°/Sec vari-speed |
| Preset | 64 preset point |
| Preset Speed | 180° per second |
| Power | |
| Power | Waterproof adaptor box, 110Vac ~220Vac |
| Operating environment | |
| Operating Temperature | -40 °C ~ 50 °C (-40 ~ 122°F) |
| Storage Temperature | -40 °C ~ 85 °C (-40 ~ 185°F) |
| Humidity | 5% ~ 95% |
| Dimension (Ø x H) | Outdoor: 246 mm x 306 mm Indoor: 175mm x 233mm |
| Outdoor Protected | IP 66 to DIN EN 60529 |
| EMI | |
| CE, UL | |



World Helmsman Technology Co., Ltd.

3F-5, No. 81, Sec. 1, Hsin Tai Wu Rd., Hsichih,
Taipei Hsien 22101, Taiwan

Tel: +886-2-2906-0816 Fax: +886-2-2904-1360

www.wh-tech.com / Email: sales@wh-tech.com

■ DISTRIBUTED BY **CE FC**

